

Qualcomm Atheros™ XB112 AR9380,

Operating System	General Features							Supported Authentication for Active associations																
	Supported version (Previous versions or v 9.0?)	Packet Capture	802.11n Capture (40 MHz)	31 Channel scanning - 5 GHz	Extended Channel- 5 GHz	Roaming Control for Survey tool	Noise detection	Open	WEP-128	LEAP-WEP	PEAP-WEP	EAP-TLS-WEP	EAP-FAST-WEP	LEAP-WPA	PEAP-WPA	EAP-TLS-WPA	EAP-FAST-WPA	LEAP-WPA2	PEAP-WPA2	EAP-TLS-WPA2	EAP-FAST-WPA2	WPA-PSK-TKIP	WPA2-PSK-AES	
Windows XP	Adapter not supported in Windows XP																							
Windows 7 (64-bit only)	v9.1	Supp	Supp	Supp	NS	Supp	Supp	Supp	Supp	Supp	NS	Supp	NS	NS	NS	Supp	NS	NS	NS	Supp	NS	NS	Supp	Supp
Windows Vista	Adapter not supported in Windows Vista																							

NS: Not supported Supp: Supported Future:Future NA: Not Applicable PS: Partial Support

1) Roaming control only supported based on signal strength